



**Skirting board
 PVC Line
 148
 172
 173**

Description

PVC Line 148, 172 and 173 are part of a range of skirting board profiles for carpeted and PVC floors.
 Art. 148 comprises two profiles - a rigid PVC base (two options to choose from) and a soft PVC clip (3 colours available).
 Used as a hygienic corner profile, once fitted and the covering relaid, it forms a rounded shield.
 It also provides an appealing finish and covering the edge of the carpet and PVC flooring, covering any potential flawed edges.
 Art. 173 is made of aluminium with an anodized silver finish.
 These profiles are recommended for communities, hospitals and schools.

Materials

Rigid PVC

Rigid PVC compound, lead-free, shock-proof, self-extinguishing. Stabilised, eco-compatible, based on Ca-Zn salts.

Plasticised PVC (soft)

Plasticised PVC compound, lead-free, self-extinguishing. Stabilised, eco-compatible, based on Ca-Zn salts.

Anodized aluminium

Al-Mg-Si aluminium, heat-treated in T6 (6060 T6)

The profiles are made by extrusion then anodized with a $\geq 15 \mu\text{m}$ thick layer.

The outer surface must be protected from scratches and rubbing. They present a strong resistance to chemical and atmospheric agents. When wet, concrete and its derivatives produce alkaline substances which can corrode metal (forming aluminium hydroxide) when allowed to react with the surface. For this reason, the visible surface of the profile must be quickly and delicately cleaned to remove any concrete, adhesive or grouting substances and detergents.

Anodized surfaces can become ruined through wear and foot traffic (profiles used on floors) and the original finish lost as a result.

Fixing

Fixing with neoprene adhesive (PVC profiles)

Remove the profile from the packaging.

Where present, also remove any protection (protective and/or shrink-wrapped film) added to protect the finish.

Measure the length required and cut the profile to this length using an appropriate tool.

Place the profile, cut to the right length, in position and fix it to the laying surface with a neoprene adhesive, making sure that the support is free of dirt and perfectly clean.

Press and hold evenly along the length of the profile to make sure it bonds correctly to the laying surface.

Installing with PP/96 type adhesive (Art. 173 only)

Remove the profile from the packaging.

Where present, also remove any protection (protective and/or shrink-wrapped film) added to protect the finish.

Measure the length required and cut the profile to this length using an appropriate tool.

Place the profile, cut to the right length, in position and fix it to the support with a suitable adhesive (such as PP/96), making sure that the support is free of dirt and perfectly clean.

Press and hold evenly along the length of the skirting board to make sure it bonds correctly to the surface.

Care and maintenance

Care and maintenance procedures for the materials used to make these profiles depends largely on the type of alloy and/or finish used.

The instructions provided below describe the operations to be performed on the profile to restore it as much as possible to its original condition.

The purpose of this document is to provide as many general indications as possible to guide you on when and how to clean the product, but they should also be verified on a case-by-case basis.

It should be pointed out there are specific responsibilities in each part of the product's life cycle, starting from when it is installed the first time.

PVC

PVC does not require special maintenance: it can be easily cleaned with colourless alcohol diluted in water or ordinary detergents.

Aluminium

No special maintenance is required and aluminium products can be easily treated with colourless alcohol in a water solution or using ordinary detergents, provided they do not contain acid (hydrochloric or hydrofluoric).

Detergent products made by multiple manufacturers and sold under a variety of commercial brands can generally be used for cleaning.

Generally speaking, there are three types of products:

- Alkaline
- Neutral
- Acid

For cleaning purposes, we recommend using a neutral detergent diluted in water then rinsing with water only, using a non-abrasive sponge and/or cloth to avoid scratching and/or damaging the anodized surface.

During cleaning, the following aspects must be kept in mind at all times:

- Do not use acid or alkaline detergents because they could damage the aluminium;
- Do not use products and/or abrasive materials;
- Do not use organic solvents on painted surfaces;
- Do not use detergents without first checking their chemical composition;
- Do not apply detergents straight onto the surface to be cleaned;
- Surfaces must be "cold" (max T° = 30°C) during cleaning and not exposed to direct sunlight;
- Detergents used in cleaning must also be "cold" (max T° = 30°C) and steam sprays should not be used.

In any case, the final stage in the cleaning process is always sufficient rinsing of the parts treated with water. They must then be immediately dried using soft fabric or leather cloths. Polishes or similar products are not required.

Clean profiles carefully as soon as required, following the instructions on the product package, to prevent any residues of concrete, grout or similar substances from attacking the surface.


Fire prevention measures

In the event of fire, use chemical fire extinguishers, dry sand or solid extinguishing agents.


Notes:

These profiles must be handled with caution, being careful to wear suitable gloves to prevent injury and/or cuts to the hands.
 The instructions and specifications provided here are the product of our experience but are only a guide, should not be considered exhaustive and must be confirmed by extensive practical applications.
 Profilpas declines any responsibility for damage to people or things resulting from improper use of the product.
 Users must establish for themselves if the product is suitable for the required used and they bear full responsibility for any incorrect installation of the material.


148 - 172 - 173




148/B +
148/C



148/BR +
148/C



172





173

PVC LINE - BASE

length = 300 cm - pack 30 pcs

ART. finishing

WHITE RIGID PVC

148/B	PVC white		19095
148/BR	PVC white		19094



no partial packaging

PVC LINE - CLIP

length = 305 cm - pack 30 pcs

ART. finishing

SOFT PVC

148/C	PVC white		19096
	PVC ash grey		19097
	PVC sand		19098


no partial packaging

PVC LINE

length = 300 cm - pack 20 pcs

ART. finishing

PVC


172	PVC white		19210
-----	-----------	---	-------

no partial packaging

length = 300 cm - pack 20 pcs

ART. finishing

ALUMINIUM

173	silver anodised		19215
-----	-----------------	---	-------

no partial packaging

MS POLYMER-BASED ADHESIVE FOR SKIRTING BOARDS

quantity 290 ml - pack 24 pcs

PP/96			78301
-------	--	--	-------

output 10/15 m for cartridge

148/C is available in different colours on request