

Skirting PVC Line

8605



8606



8615



8616



Description

PVC Line 8605, 8606, 8615 and 8616 are a range of a non-toxic and shockproof coextruded PVC (expanded + rigid) skirting board, foiled with UV resistant Alcom® Plus decorative film.

They must be laid using suitable adhesives (type PP/96).

The PVC Line 8605 series is available in 58 different colors, both plain color and wood decoration, in order to suit any type of floor decor. PDS technology also allows customization on demand with infinite solutions.

In addition to the decorative function, it meets the technical requirement to hide the perimeter expansion space in floating flooring.

PVC Line 8605, 8616, 8615 and 8616 does not contain formaldehyde (UNI EN 717-2 1996:1996), can be used in humid environments (water absorption <1% UNI EN ISO 62:2008), resists the cold liquid aggression (UNI EN 12720:2009).

Materials

Compound PVC vinyl foam lead-free, self-extinguishing. Stabilized eco-compatible salt-based Ca-Zn.

Laying

Laying instructions using Adhesives Type PP/96

Take the skirting board out of the packaging.

Measure and cut the skirting board to the required length with the proper tools.

Verifying that the laying area is perfectly clean and then place the skirting board, now cut to measure, in the correct position, fixing it to the wall with the appropriate adhesive (type PP/96).

Keep sufficiently pressure for a few minutes on the entire length of the skirting board in order to ensure sufficient adhesion to the laying surface.

Care and maintenance

The instructions below describe the operations in order to maintain as much as possible the original appearance of the product.

The intent is to provide all those general guidelines that can serve in the choice of when and how to clean, but they will have to be checked case by case. It must be underlined that, at every stage of product life starting from its installation, there are already definite responsibilities.

PVC - These need no particular maintenance and are easily cleaned with colorless alcohol diluted in water, or with normal detergents diluted in water (though not acid-based products); rinse thoroughly when finished, with water only.

Use a sponge and/or non-abrasive cloth to prevent scratches and/or damage to the surface.

Fire control measures

In case of fire, extinguish with fire-fighting chemical products, dry sand or solid fire-extinguishing agents.

Note

These profiles must be handled with care, taking the necessary steps to use suitable gloves to prevent wounds, such as cuts to the hand.

All indications and instructions herein contained, that comes from our own experience, has to be understood as purely informative and will have to be confirmed through exhaustive practical experience.


Profilpas will not be held responsible for any personal injury or material damage from improper use of the product.

The user is responsible for establishing whether the product is suitable for the task and likewise must assume all responsibility for incorrect laying of material.

8605 – 8606



8606 white RAL 9003 co-extruded PVC



8605

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.

8605		white RAL 9003	29175		black RAL 9004	29176
		white RAL 9010	29177			
8605		silver	29178			

no partial packaging

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.

		decors			
8605		96 white RAL 9010 embossed		29030	
		97 black RAL 9005 embossed		29031	
8605		99 satin silver		29035	
		100 satin steel		29036	

no partial packaging

PVC LINE

length = 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.	decors		decors		decors		decors	
8605		02 29000		41 29012		1006 29102		1060 29120
		08 29001		44 29013		1009 29103		1063 29121
		09 29002		47 29033		1012 29104		1066 29122
		10 29003		48 29015		1021 29107		1069 29123
		11 29004		65 29018		1024 29108		1081 29127
		12 29005		76 29020		1030 29110		1084 29128
		20 29006		77 29021		1033 29111		1087 29129
		25 29032		78 29022		1036 29112		1090 29130
		32 29007		80 29023		1042 29114		1105 29135
		34 29008		81 29024		1045 29115		1108 29136
		35 29009		92 29026		1051 29117		1111 29137
		36 29010		95 29029		1054 29118		
		40 29011		1003 29101		1057 29119		

no partial packaging - 8605 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters €/m 3,72

PVC LINE


length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.

8606		white RAL 9003	29227		black RAL 9004	29228
		white RAL 9010	29229			
8606		silver	29230			


no partial packaging - 8606 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters



8605 covered with Alcrom® Plus film



8605 foam PVC covered with Alcrom® Plus film



8606


8615 – 8616



8616 black RAL 9004 co-extruded PVC



8615 silver co-extruded PVC







8615

PVC LINE


length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.

8615		white RAL 9003	29353		black RAL 9004	29354
		white RAL 9010	29355			
8615		silver	29356			

no partial packaging



8615 decors with film Alcrom® Plus

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm


CO-EXTRUDED PVC (FOAM PVC + RIGID PVC) COVERED WITH ALCROM® PLUS FILM

ART.

8615	decors		
		96 white RAL 9010 embossed	29357
		97 black RAL 9005 embossed	29358

no partial packaging

8615 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters







8616

PVC LINE

length 250 cm - pack 20 pcs - H = 70 mm

CO-EXTRUDED PVC (FOAM PVC + RIGID PVC)

ART.

8616		white RAL 9003	29495		black RAL 9004	29496
						
8616		silver	29498			

no partial packaging

8616 can be covered with customised Alcrom® Plus film on request, with a minimum order of 500 meters